

WO0237995

BEST AVAILABLE COPY

Publication Title:

A SHOCK ABSORBING DEVICE FOR A SHOE

Abstract:

According to the invention there is provided a shock-absorbing device for an article of footwear. The device includes a frame having a heel supporting region for supporting a heel portion of the article of footwear, and a ball supporting region for supporting a ball portion of the article of footwear. The heel supporting region includes a pair of cushioned soles each having a tread that is arcuate in shape, and the ball supporting region also includes a pair of cushioned soles each having a tread that is arcuate in shape. The arcuate shape of the treads allow movement of air within the cushions, to properly cushion a user's walk.

Data supplied from the esp@cenet database - <http://ep.espacenet.com>

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 May 2002 (16.05.2002)

PCT

(10) International Publication Number
WO 02/37995 A1

(51) International Patent Classification⁷: **A43B 13/18**,
3/16, 5/18, A63B 25/10

(21) International Application Number: PCT/IB01/02116

(22) International Filing Date:
9 November 2001 (09.11.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2000/6470 9 November 2000 (09.11.2000) ZA

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN,
YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,
TG).

(71) Applicant and

(72) Inventor: **WOOD, Charles, Ogilvie** [ZA/ZA]; 2 Topaz
Lincoln Street, Khyber Rock, 2157 Sandton (ZA).

Published:


— with international search report
— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

(74) Agents: **GILSON, David, Grant** et al.; Spoor and Fisher,
P.O. Box 41312, 2024 Craighall (ZA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: A SHOCK ABSORBING DEVICE FOR A SHOE



(57) Abstract: According to the invention there is provided a shock-absorbing device for an article of footwear. The device includes a frame having a heel supporting region for supporting a heel portion of the article of footwear, and a ball supporting region for supporting a ball portion of the article of footwear. The heel supporting region includes a pair of cushioned soles each having a tread that is arcuate in shape, and the ball supporting region also includes a pair of cushioned soles each having a tread that is arcuate in shape. The arcuate shape of the treads allow movement of air within the cushions, to properly cushion a user's walk.



WO 02/37995 A1

A SHOCK ABSORBING DEVICE FOR A SHOE

BACKGROUND OF THE INVENTION

THIS invention relates to a shock-absorbing device for an article of footwear, such as a shoe.

SUMMARY OF THE INVENTION

According to a first aspect of the invention there is provided a shock-absorbing device for an article of footwear, the device including a frame having:

- a) a heel supporting region for supporting a heel portion of the article of footwear, and a ball supporting region for supporting a ball portion of the article of footwear; and
- b) a first cushioned sole located at the heel supporting region of the frame, and a second cushioned sole located at the ball region of the frame.

Advantageously, the frame is adjustable so that the distance between the heel supporting and ball supporting regions may be varied.

Preferably, the frame is rigid.

Advantageously, each cushioned sole has a tread that is arcuate in shape.

Conveniently, the heel and ball supporting regions of the frame each include a pair of pneumatically cushioned soles with arcuate treads.

Advantageously, the cushioned soles are removable from the frame and are in the form of inserts.

Conveniently, the device is releasably attachable to the article of footwear.

According to a second aspect of the invention there is provided a shock-absorbing device for an article of footwear, the device including a frame for

attachment to a heel region of the article of footwear, the frame including a pair of cushioned soles each having a tread which is arcuate in shape.

The invention also relates to a frame for attachment to a ball portion of an article of footwear, the frame including a pair of cushioned soles, each having treads which are arcuate in shape.

BRIEF DESCRIPTION OF THE DRAWINGS

- Figure 1** is a side view of a shock-absorbing device according to a first embodiment of the invention;
- Figure 2** is a bottom view of Figure 1;
- Figure 3** is a pictorial view of a cushioned insert for the shock-absorbing device shown in Figure 1;
- Figure 4** is a cross-sectional view on the line 4 - 4 in the device of Figure 1;
- Figure 5** is a pictorial view of a bracket for attaching the device shown in Figure 1 to the shoe of a user; and
- Figure 6** is a side view of a shock-absorbing device according to a second embodiment of the invention.

DESCRIPTION OF EMBODIMENTS

Referring to Figures 1 and 2, a shock-absorbing device 10 is provided for supporting an article of footwear such as shoe 12 (shown in dotted outline together with a foot in the shoe in Figure 1).

The shock-absorbing device 10 comprises a rigid frame 14, which supports cushion inserts 16, a bracket 18 and first and second straps 19 and 20 for attaching the shock-absorbing device 10 to the shoe 12. The frame 14 may be made from aluminium or kevlar re-inforced fiberglass, or any other lightweight rigid material. The cushion inserts 16 fit into receptacles 21 in the frame 14.

The frame 14 includes two support regions 22 and 24. The support region 22 is for supporting the heel of the foot of a person using the device 10 and the support region 24 is for supporting the ball of the foot of a person using the device 10. Thus, the support region 22 is termed the "heel support region" and the support region 24 is termed the "ball support region". The support regions 22 and 24 are joined by an adjustable neck region 26. The length of the neck region 26 may be adjusted to adjust the spacing between the inserts 16 on the support regions 22 and 24.

Referring to Figure 3, each insert 16 is hollow and is made from rubber. The insert 16 has an arcuate tread 32 and a groove 34, extending around the insert. The insert 16 is hollow, and thus has a hollow cavity 35. The hollow cavity 35 may be left hollow, or it may contain a spongy material, or it may receive a bladder, which may be inflated by air. A pair of inserts 16 is arranged to support the heel or ball of the foot of a user, and each is about 6 to 8, preferably 7 cm in length, and 2 to 4, preferably 3 cm in width.

-5-

Referring to Figure 4, the insert 16 is designed to fit into a receptacle 28 on the device 10. A projection 34 extends from the inner wall of the receptacle 28 into the groove 34 of the insert 16, to lock the insert 16 within the receptacle 28. In the case where a bladder is provided within the cavity 35, the bladder may be inflated via a valve which extends through a hole in the insert 16, to a pressure of 2 to 10 bar, but will usually be in the region of 2 bar. The insert 16 is locked within the housing, when inflated. If an insert 16 is punctured, it may be replaced with a new insert, or the insert may be repaired. Further, the inserts 16 are oriented in the frame 16, so that the arcs defined by the arcuate shapes of the treats 34 of the inserts 34 are parallel with an axis "a" running through the frame 14.

Referring to Figure 5, a bracket 18 for attaching the device 10 to the shoe of a user (not shown) includes a base portion 38 which is attached, or attachable to the heel support region 22 on the frame 14 of the device 10 shown in Figure 1. The base region 38 is arranged to receive and support the sole of the shoe shown in Figure 1. The bracket 18 includes an adjustable rear wall 40 which is arranged to abut with the back of the heel of a shoe, and adjustable side walls 42 and 44 which are arranged to abut with and engage with the side portions of the heel of a shoe. A strap 19 which comprises a first strap 19a having hook material and a second strap 19b having loop material is provided for strapping the bracket 18 to the heel portion of a shoe.

Referring to Figures 1 and 2, the inserts 16 are arranged to form a first pair at the heel support region 22 which supports the heel of a foot of a user, and a second pair at the ball support region 24 which supports the ball of the foot of a user. The adjustability of the neck region 26 of the frame 14, allows the device 10 to be adjusted for different size feet and shoes 12. The positioning of the insert 16 under the heel and the ball of a foot of a user is important. During walking, the heel of the foot supports the weight of the body when the ball of the foot is off the ground, and the ball of the foot supports the weight of the

body when the heel is off the ground. Thus, the device 10 provides cushioning at the crucial parts of the foot during walking. The rigid frame 14 is also important to support the shoe and foot and provide a comfortable walk. It is also important that the inserts are arcuate in shape to provide proper cushioning during walking. The arcuate shape allows the movement of air within the bladders of the inserts 16, to properly cushion a user's walk.

Although the device 10 according to the invention is shown with the heel support region 22 and ball support region 24 connected by a neck region 26, it is also possible to have separate heel and ball support regions 22 and 24 which are shown in Figure 6. A user may elect to use only the heel support region 22. The separate heel and ball support region are very similar to the device described above in Figure 1, except the supports are not connected, and thus work in much the same way.

CLAIMS

1. A shock-absorbing device for an article of footwear, the device including a frame having:
 - a) a heel supporting region for supporting a heel portion of the article of footwear, and a ball supporting region for supporting a ball portion of the article of footwear; and
 - b) a first cushioned sole located at the heel supporting region of the frame, and a second cushioned sole located at the ball region of the frame.
2. A device according to claim 1, wherein the frame is adjustable so that the distance between the heel supporting and ball supporting regions may be varied.
3. A device according to claim 1 or 2, wherein the frame is rigid.
4. A device according to any one of the preceding claims, wherein each cushioned sole has a tread that is arcuate in shape.
5. A device according to claim 4, wherein heel and ball supporting regions of the frame each include a pair of cushioned soles with arcuate treads.
6. A device according to any one of the preceding claims, wherein the cushioned soles are removable from the frame and are in the form of inserts.
7. A device according to any one of the preceding claims, which is releasably attachable to the article of footwear.

8. A shock-absorbing device for an article of footwear, the device including a frame for attachment to a heel region of the article of footwear, the frame including a pair of cushioned soles each having a tread which is arcuate in shape.
9. A shock-absorbing device for an article of footwear, the device including a frame for attachment to a ball region of the article of footwear, the frame including a pair of cushioned soles, each having a tread which is arcuate in shape.

1/2






FIG 3




FIG 4





FIG 5

INTERNATIONAL SEARCH REPORT

Inten Application No

PC1 / /02116

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A43B13/18 A43B3/16 A43B5/18 A63B25/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A43B A63B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 980 145 A (CHRISTOPHER COLLARO) 13 January 1965 (1965-01-13) the whole document ---	1-4, 6, 7
X	NL 8 502 659 A (MATHEUS HUBERTUS GERARDUS KIER) 16 April 1987 (1987-04-16) claims 1,11 page 5 ---	1, 7, 8
X	US 4 660 299 A (OMILUSIK DALE) 28 April 1987 (1987-04-28) the whole document ---	1, 4, 5
Y	US 4 774 776 A (GULLI FRANK) 4 October 1988 (1988-10-04) the whole document ---	8, 9
Y	US 4 774 776 A (GULLI FRANK) 4 October 1988 (1988-10-04) the whole document ---	8, 9
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the International filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the International filing date but later than the priority date claimed

"T" later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the International search

15 March 2002

Date of mailing of the international search report

26/03/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Claude1, B

INTERNATIONAL SEARCH REPORT

Intern: Application No.
PCT/ /02116

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 151 202 A (GEORGE FREDERICK STORY) 23 September 1920 (1920-09-23) the whole document -----	8,9

INTERNATIONAL SEARCH REPORT

tion on patent family members

Intern: Application No

PCT/ /02116

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 980145	A	13-01-1965	NONE	
NL 8502659	A	16-04-1987	NONE	
US 4660299	A	28-04-1987	NONE	
US 4774776	A	04-10-1988	AU 4439185 A EP 0181919 A1 WO 8505256 A1	13-12-1985 28-05-1986 05-12-1985
GB 151202	A	23-09-1920	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.